


**ACUDOR**

www.acudor.com  
U.S.A.: info@acudor.com / 800.722.0501  
CANADA: info@acudor.ca / 844.228.3671  
INTERNATIONAL: info@acudorintl.com  
(905) 428.2240

**FB-5060-DW****FIRE RATED - FOR WALLS**

QTY.	NOMINAL SIZE	A	B	C	D	E	F	LOCK
	8 X 8 (203 X 203)	7.78 (198)	7.78 (198)	10.62 (270)	10.62 (270)	8.12 (206)	8.12 (206)	1
	10 x 10 (254 x 254)	9.78 (248)	9.78 (248)	12.62 (321)	12.62 (321)	10.12 (257)	10.12 (257)	1
	12 x 12 (305 x 305)	11.78 (299)	11.78 (299)	14.62 (371)	14.62 (371)	12.12 (308)	12.12 (308)	1
	14 x 14 (356 x 356)	13.78 (350)	13.78 (350)	16.62 (422)	16.62 (422)	14.12 (359)	14.12 (359)	1
	16 x 16 (406 x 406)	15.78 (401)	15.78 (401)	18.62 (473)	18.62 (473)	16.12 (409)	16.12 (409)	1
	18 x 18 (457 x 457)	17.78 (452)	17.78 (452)	20.62 (524)	20.62 (524)	18.12 (460)	18.12 (460)	1
	24 x 24 (610 x 610)	23.78 (604)	23.78 (604)	26.62 (676)	26.62 (676)	24.12 (613)	24.12 (613)	1

**WALLS**

Approved by Underwriters Laboratories (UL) for 1 1/2 hours "B" label in walls and ULC for 2 hours "B" label in walls.



**STANDARD FEATURES:** UNIVERSAL SELF LATCHING BOLT- OPERATED BY KNURLED KNOB / FLUSH KEY/ AND INSIDE TURN RELEASE.  
**OPTIONS:** CARBON STEEL

**LOCK TYPE**

- ☐ RIM CYLINDER LOCK  
☐ PREPARED FOR MORTISE CYLINDER LOCK

- ☐ STAINLESS STEEL  
☐ OTHER

**ALL FIRE RATED:**

SPECIAL SIZES CAN BE ORDERED, BUT BASIC CONSTRUCTION MUST REMAIN CONSTANT TO COMPLY WITH UL AND ULC REGULATIONS.

**FINISH**

- ☐ Baked White Prime Coat  
(Additional finish paint is recommended for superior corrosion resistance).

JOB NAME:

APPROVED BY:

CUSTOMER:


DATE:

**ACUDOR**

www.acudor.com  
U.S.A.: info@acudor.com / 800.722.0501  
CANADA: info@acudor.ca / 844.228.3671  
INTERNATIONAL: info@acudorintl.com  
(905) 428.2240

**FB-5060-DW****FIRE RATED - FOR WALLS**

QTY.	NOMINAL SIZE	A	B	C	D	E	F	LOCK
	22 x 30 (559 x 762)	29.78 (756)	21.78 (553)	24.62 (625)	32.62 (829)	22.12 (562)	30.12 (765)	2
	22 x 36 (559 x 914)	35.78 (909)	21.78 (553)	24.62 (625)	38.62 (981)	22.12 (562)	36.12 (917)	2
	24 x 36 (610 x 914)	35.78 (909)	23.78 (604)	26.62 (676)	38.62 (981)	24.12 (613)	36.12 (917)	2
	24 x 48 (610 x 1219)	47.78 (1214)	23.78 (604)	26.62 (676)	50.62 (1286)	24.12 (613)	48.12 (1222)	2
	30 x 30 (762 x 762)	29.78 (756)	29.78 (756)	32.62 (829)	32.62 (829)	30.12 (765)	30.12 (765)	2
	36 x 36 (914 x 914)	35.78 (909)	35.78 (909)	38.62 (981)	38.62 (981)	36.12 (917)	36.12 (917)	2
	36 x 48 (914 x 1220)	47.78 (1214)	35.78 (909)	38.62 (981)	50.62 (1286)	36.12 (917)	48.12 (1222)	2

**WALLS**

Approved by Underwriters Laboratories (UL) for 1 1/2 hours "B" label in walls and ULC for 2 hours "B" label in walls.



**STANDARD FEATURES:** UNIVERSAL SELF LATCHING BOLT- OPERATED BY KNURLED KNOB / FLUSH KEY/  
**OPTIONS:** AND INSIDE TURN RELEASE,  
CARBON STEEL,

**LOCK TYPE**

- ☐ RIM CYLINDER LOCK  
☐ PREPARED FOR MORTISE CYLINDER LOCK

- ☐ STAINLESS STEEL  
☐ OTHER

**ALL FIRE RATED:**

SPECIAL SIZES CAN BE ORDERED, BUT BASIC CONSTRUCTION  
MUST REMAIN CONSTANT TO COMPLY WITH UL AND ULC REGULATIONS.

**FINISH**

- ☐ Baked White Prime Coat  
(Additional finish paint is recommended for superior corrosion resistance).

JOB NAME:

APPROVED BY:

CUSTOMER:

DATE: